DOORS AND OPENINGS - DIVISION 08 Accordion Folding Doors - 08 35 14

Part 1 General

1.1 Summary

.1 Unless otherwise indicated, follow the standards below when specifying work for folding doors. These standards are not intended to restrict or replace professional judgment.

1.2 Design Requirements

.1 Specify finishes with class A flame spread.

1.3 Guarantee

.1 The products described in this section shall be guaranteed for a period of (2) two years against fabrication or installation. Pantographic frame, rails, and chariot for a period of ten (10) years from the date of substantial performance of the work.

Part 2 Products

2.1 Preferred Products

.1 Refer to MAT website (<u>www.materialanalysis.ca</u>) for selection of products for this section, except for prescribed items. Products selected on MAT should have score of 5 or above.

2.2 Materials

- .1 The assembly shall be a joining pair of fixed-jamb partitions that attach and stack at opposite jambs and join in the center.
- .2 Panels hall be specially laminated engineered wood core, bonded with water-resistant plastic glue and surfaced with Walnut wood veneer.
- .3 Panels shall be hinged and edge sealed with heavy-duty, dual wall, flame resistant, extruded vinyl. Hinges shall be securely locked into and protect the panel edges. They shall provide "memory-action" causing panels to extend and stack equally, smoothly and quietly. Color shall be brown
- .4 Hardware shall include handles, touch-bar automatic latches and all necessary screws and fasteners

2.3 Track and Hanger Assembly

- .1 Track shall be extruded aluminum, surface mounted, decorated type.
- .2 Specify hanger assembly with two wheels suspended on alternate panels. A four wheel truck hanger shall be installed on each end post. Wheels shall be ball-bearing.

January, 2014 Page 1 of 2



BUILDING DESIGN STANDARDS

DOORS AND OPENINGS - DIVISION 08 Accordion Folding Doors - 08 35 14

2.4 Accordion Folding Partitions

.1 For STC 25 to 30, accordion partition shall be manually operated, "Scale /6", wood type as manufactured by Panelfold Canada Inc. or other approved equivalent.

END OF SECTION 08 35 14

January, 2014 Page 2 of 2